CLAMPING AND BRAKING ELEMENTS | PNEUMATIC SERIES LBPS

PRODUCT ADVANTAGES



broad range of products

For all common profile rail guides

- Energize to open (NC) through spring-loaded energy storage
- high durability
 Up to 5 million static clamping cycles
- Small and narrow design
 By using U-form piston
- Safety element
 Safe braking in case of energy failure

THE BEST PRODUCT FOR YOUR APPLICATION		
APPLICATION SCE- NARIOS	 Clamping in case of pressure drop Braking linear motors Clamping without energy requirement 	
FURTHER INFORMATION	 Spacer plate In addition, a spacer plate might have to be ordered as height compensation, depending on the height of the rail carriage (dimension D). Special variants on request, e.g. With proximity switch monitoring With low opening pressure (3.0 bar or 4.0 bar) With additional air connection (from above, from the front) 	

BENEFITS IN DETAIL

1 Profile rail guide

- Available for all common profile rail guides

2 Wedge-type gear

- Power transmission between the pistons and clamping jaws and brake shoes

3 Clamping jaws and brake shoes

- Pressed at the free surfaces of the profile rail guide

4 Narrow housing


- chemically nickel plated steel

5 Pneumatic piston

- The piston moves the wedge-type gear longitudinally

6 Spring-loaded energy storage

- For non-pressurized closing of the clamping unit



INFORMATION ON THE SERIES

TECHNICAL DATA

Rail size	15-35 mm
Holding force	400-1900 N
Pressure min. / max.	5.5 / 6.5
Spring storage	existing
PLUS connection	No
Static clamping cycles (B10d value)	up to 5 million
Dynamic braking cycles	up to 500
Operation	pneumatic
Operating temperature	-10 +70 [°C]



Technical Information

All information just a click away at: www.zimmer-group.de Find data, illustrations, 3D models and operating instructions for your installation size using the order number for your desired model. Quick, clear and always up-to-date.

Selection guide for clamping and braking elements Whatever the possible application – here, you'll find the right product. Easy selection of the right element for any rail-carriage combination: www.zimmer-group.de/de/plt.